



IDENTITY (As Used on Label and List)

ComCork™ Flooring

Section I

Manufacturer's/Supplier Name: US OFFICE: Sustainable Flooring, Inc	Emergency Telephone Number: (303) 544-6076
Address (Number, Street, City, State, and ZIP Code) 4390 Pali Way; Boulder, CO 80301	Telephone Number for Information (303) 544-6076
	Date Prepared May 25, 2017

Section II - Hazardous Ingredients/Identity Information

Hazardous Components (Specific Chemical Identity; Common Name(s))	Amount in product	OSHA PEL	ACGIH TLV	Other Limits Recommended
Cork agglomerate and veneer	35.5% by volume	15 mg/m ³ for total dust; 5 mg/m ³ respirable fraction of wood dust ¹	1 mg/m(3) – for 8 hour work day ²	NIOSH REL: 1 mg/m(3) – for 10 hour work day ³
Polymerized Polyurethane binder (for bonding cork agglomerate)	3% by volume	Not Listed	Not Listed	Not applicable
Wood Flour (in High Density Fiberboard)	50.5 %	15 mg/m ³ for total dust; 5 mg/m ³ respirable fraction of wood dust ⁴	1 mg/m(3) – for 8 hour work day ⁵	NIOSH REL: 1 mg/m(3) – for 10 hour work day ⁶
UMF Resin (Urea Melamine Formaldehyde; bonding agent of High Density Fiberboard)	4%	Not Listed	Not Listed	Not applicable
Paraffin Wax (in High Density Fiberboard)	0.75-1%	Not applicable	Not applicable	Not applicable
Phenol Formaldehyde (in High Density Fiberboard)	<0.005%; .02 ppm (Chamber test results)	TLV-STEL: 0.3 ppm, 0.37 mg/m ³		
Polyvinyl chloride (mixed with plasticizers, limestone, stabilizers and additives)	6%	Not Known	Not Known	Not Known



1-3 OCCUPATIONAL SAFETY AND HEALTH GUIDELINE FOR WOOD DUST, ALL SOFT AND HARDWOODS, EXCEPT WESTERN RED CEDAR
4-6 Parts of vapor or gas per million parts of contaminated air by volume at 25 [deg]C and 760 torr. (**Gases, vapors, fumes, dusts, and mists. - 1926.55 App**).

Section III - Physical/Chemical Characteristics ⁷

Boiling Point	No Data	Density of HDF	800-950 kg/m ³
Auto Ignition Temperature	175° C	Melting Point/Evaporation Rate	No Data
Solubility in Water Not Applicable			
Appearance and Odor Natural cork color with an odor of wood			

Section IV - Fire and Explosion Hazard Data

General Cork Floating floors do not present any special risk and are not an explosion hazard. Sanding, sawing or machining can result in the generation of wood and cork dust that can present a strong explosion hazard if a dust cloud contacts an ignition source.	
Extinguishing Media Water, carbon dioxide, sand or dry chemical	
Special Fire Fighting Procedures None	
Unusual Fire and Explosion Hazards None	

Section V - Reactivity Data

Stability Yes	Conditions to Avoid Not applicable to product in its' supplied form.
Incompatibility (<i>Materials to Avoid</i>) Not applicable	
Hazardous Decomposition or Byproducts Byproducts emitted by decomposition include carbon monoxide, carbon dioxide, aliphatic aldehydes, polycyclic aromatic hydrocarbons, rosin acids, and terpenes.	

Section VI - Health Hazard Data



1) Wood Dust:

Both the skin and respiratory system can become sensitized to wood dust. When a worker becomes sensitized to wood dust, he or she can suffer a severe allergic reaction (such as asthma) after repeated exposure or exposure to lower concentrations of the dust.

Other common symptoms associated with wood dust exposure include eye irritation, nasal dryness and obstruction, prolonged colds, and frequent headaches.

Certain species of hardwood - such as oak, mahogany, beech, walnut, birch, elm, and ash - have been reported to cause nasal cancer in wood-workers. This is particularly true when exposures are high. The American Conference of Governmental Industrial Hygienists (ACGIH) recognizes wood dust as a "confirmed" human carcinogen,³ and recommends a limit of 1 milligram per cubic meter (mg/m³) for hardwoods and 5 mg/m³ for softwoods. At this time, OSHA regulates wood dust as a nuisance dust; however, OSHA strongly encourages employers to keep exposures to a minimum and to adopt the ACGIH levels. The maximum permissible exposure for nuisance dust is 15 mg/m³, total dust (5 mg/m³, respirable fraction).

2) Formaldehyde:

Formaldehyde is considered a strong irritant and potent sensitizer. Inhalation of large amount of HCHO can cause severe irritation of the upper respiratory tract and death. Data from human exposures indicate that exposure to large concentrations of HCHO gas may lead to pulmonary edema. Even HCHO gas present in the workroom at concentrations of 1 to 11 ppm can cause eye, nose, and throat irritation (5.11.). Formaldehyde has the potential to cause cancer in humans (5.12.).

Route(s) of Entry: Mouth, Skin, eyes	Inhalation? Yes	Skin? Yes	Ingestion? Yes												
Health Hazards (<i>Acute and Chronic</i>) Formaldehyde is considered a strong irritant and potent sensitizer. Inhalation of large amount of HCHO can cause severe irritation of the upper respiratory tract and death. Data from human exposures indicate that exposure to large concentrations of HCHO gas may lead to pulmonary edema. Even HCHO gas present in the workroom at concentrations of 1 to 11 ppm can cause eye, nose, and throat irritation.															
Carcinogenicity: Formaldehyde has the potential to cause cancer in humans. Avoid high concentrations and prolonged exposure.															
Signs and Symptoms of Exposure <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 50%; text-align: left;">Concentration</th> <th style="width: 50%; text-align: left;">Symptoms</th> </tr> </thead> <tbody> <tr> <td>0.5 to 2 ppm</td> <td>eyes, nose and throat irritation</td> </tr> <tr> <td>3 to 5 ppm</td> <td>tearing of the eyes</td> </tr> <tr> <td>10 to 20 ppm</td> <td>difficult breathing, nose and throat burning, cough, heavy tearing of the eyes</td> </tr> <tr> <td>25 to 30 ppm</td> <td>severe respiratory tract injury</td> </tr> <tr> <td>100 ppm</td> <td>immediately dangerous to life and health (IDLH)</td> </tr> </tbody> </table>				Concentration	Symptoms	0.5 to 2 ppm	eyes, nose and throat irritation	3 to 5 ppm	tearing of the eyes	10 to 20 ppm	difficult breathing, nose and throat burning, cough, heavy tearing of the eyes	25 to 30 ppm	severe respiratory tract injury	100 ppm	immediately dangerous to life and health (IDLH)
Concentration	Symptoms														
0.5 to 2 ppm	eyes, nose and throat irritation														
3 to 5 ppm	tearing of the eyes														
10 to 20 ppm	difficult breathing, nose and throat burning, cough, heavy tearing of the eyes														
25 to 30 ppm	severe respiratory tract injury														
100 ppm	immediately dangerous to life and health (IDLH)														
Medical Conditions Generally Aggravated by Exposure.															
Emergency and First Aid Procedures Seek medical attention if above referenced symptoms occur.															

Section VII - Precautions for Safe Handling and Use



Steps to Be Taken in Case Material is Released or Spilled
Not applicable to product in its' supplied form.

Waste Disposal Method
No special disposal methods are required.

Precautions to Be taken in Handling and Storing
No special precautions are required for products in their supplied form. Keep material in a cool, dry, and ventilated place. Clean site of airborne dust as it is created to minimize airborne dust and contaminant issues.

Section VIII - Control Measures

Respiratory Protection (*Specify Type*)
No special handling precautions are required for products in their supplied form, though use of an acceptable NIOSH respirator is recommended to avoid inhalation of excess dust particles.

Ventilation
When milling, dust containment and adequate ventilation are requested.

Eye Protection
No special handling precautions are required for products in their supplied form, though use of protective eye protection is recommended when milling (cutting, shaping, etc.) to avoid discomfort and the potential of airborne dust to affect sight.

Other Protective Clothing or Equipment
No special protective clothing or equipment is required for products in their supplied form.

Section IX – Toxicology Information

Not available for products in their supplied form

Section X - Control Measures

Not available for products in their supplied form

Section XI – Ecological Considerations

Not applicable.

Section XII – Disposal Considerations

Follow applicable local, state, and federal guidelines for disposal.

Section XIII –Transportation Considerations

Not regulated as a hazardous material by the United States Department of Transportation in its supplied state.



SUSTAINABLE
F L O O R I N G

Section XIV –Additional information

IMPORTANT: The information and data included in this report is believed accurate, and has been compiled through information and testing created for the manufacturing facility producing said material, as well as through conversations with OSHA, as well as through OSHA's detailed technical manuals, and information provided by other technical experts. Buyer assumes all risk of use, storage and handling of the product in compliance with applicable local, state, and federal regulations. **NOTE: Sustainable Flooring, Inc. makes no warranty, of any kind, express or implied, concerning the accuracy and completeness of the information contained within, and will not be liable for claims relating to any party's reliance on this information.**