

CSI Spec. for Textura Dimensions Wall Panels (06 4200)

Textura Recycled Wood Panels

Part 1 – General

1.03 QUALITY ASSURANCE

A. Qualifications:

1. Installer Qualifications:
 - a. Minimum 2 years of work with the installation of products in this section.

1.04 DELIVERY, STORAGE, AND HANDLING

A. Deliver wall paneling to project site, or fabrication site, not less than 2 days prior to start of installation (to allow for suitable acclimation).

B. Environmental Requirements: Maintain and following conditions in building for minimum 7 days prior to, during and after installation of panels.

1. Temperature: 60 to 72 degrees F (16 to 22 degrees C)
2. Humidity: 25 to 55 percent

1.06 WARRANTY

A. Special Warranty:

1. Sustainable Flooring's Structural Warranty: 5 years against delamination or separation as a result of a manufacturing defect when finished and maintained in accordance with manufacturer's installation instructions.

PART 2 – PRODUCTS

2.01 MANUFACTURER

- A. Sustainable Flooring
4390 Pali Way
Boulder, CO 80301
- Tel: (303) 544-6076
Fax: (303) 447-0491
e-mail: info@sustainableflooring.com
Website: <http://www.sustainableflooring.com>

B. Substitutions: None Permitted

2.02 MATERIALS

A. Textura Dimensions

1. Available Options
 - a. Textura Dimensions **Split Cube Oak - Grande**
 - b. Textura Dimensions **Split Cube Oak - Micro**
 - c. Textura Dimensions **Split Strip Oak**
 - d. Textura Dimensions **Split Strip Ash**
 - e. Textura Dimensions **Split Strip Walnut**
 - f. Textura Dimensions **Chatter Walnut**

g. Textura Dimensions **Sanitas Mix**

2. Size:

a. Textura Dimensions **Split Cube Oak - Grande:**

Cube size: 75mm x 75mm (approx. 3"x3")

Panel size: 14-33mm x 300m x 300mm (approx. ½"-1-1/3" thickness x 12" x 12").

b. Textura Dimensions **Split Cube Oak - Micro:**

Cube size: 50mm x 50mm (approx. 2"x2")

Panel size: 14-33mm x 300m x 300mm (approx. ½"-1-1/3" thickness x 12" x 12").

c. Textura Dimensions **Split Strip Oak:**

Strip Thickness (top layer): 3-22mm (approx. 1/8"-7/8")

Panel size: 14-33mm x 300m x 600mm (approx. ½"-1-1/3" thickness x 12" x 24").

d. Textura Dimensions **Split Strip Ash:**

Strip Thickness (top layer): 3-22mm (approx. 1/8"-7/8")

Panel size: 14-33mm x 300m x 600mm (approx. ½"-1-1/3" thickness x 12" x 24").

e. Textura Dimensions **Split Strip Walnut:**

Strip Thickness (top layer): 3-22mm (approx. 1/8"-7/8")

Panel size: 14-33mm x 300m x 600mm (approx. ½"-1-1/3" thickness x 12" x 24").

f. Textura Dimensions **Chatter Walnut:**

Strip Thickness (top layer): 3-17mm (approx. 1/8"-3/4")

Panel size: 14-28mm x 300m x 600mm (approx. ½"-1-1/8" thickness x 12" x 24").

g. Textura Dimensions **Sanitas Mix:**

Strip Thickness (top layer): 4-15mm (approx. 1/6"-5/8")

Panel size: 15-26mm x 300m x 600mm (approx. 5/8"-1" thickness x 12" x 24").

* Other widths, thickness, and lengths are available upon special order.

3. Construction: Textura Dimensions is made of decorative placed wood strips laminated onto a multi-ply substrate

4. Finish:

a. Unfinished (standard option)

1. Product to remain unfinished

2. Finish to be applied onsite (inquire as to recommendations)

b. Prefinished

1. Product to be 'prefinished' at the factory

a. Natural Oil

b. Urethane

2. Product to be supplied with a recommended coating via intermediary (inquire as to options)

a. Natural Oil

b. Urethane

c. Fire-retardant finish

PART 3 - EXECUTION

3.01 EXAMINATION

- A. Examine components and/or surface to which Textura Dimensions will be mounted on, or fabricated with, ensuring components are clean, dry, flat, and free of contaminants that could potentially interfere with adhesive bond.
- B. Verify that HVAC system is operating and maintaining occupancy level temperature and humidity conditions.
- C. If either of the above needs attendance, coordinate with responsible entity to correct unsatisfactory conditions prior to the beginning of the installation.

3.02 PREPARATION

- A. Acclimatization: Ensure that all Textura products are acclimated for a minimum of 3 days (unboxed and within the space to which the material will be installed).

3.03 INSTALLATION

- A. Install in accordance with manufacturer's installation instructions.
 - 1. Set paneling plumb, rigid and level
 - a. Ensure all penetrations and obstructions are accounted for in the layout
 - 2. Install panels using adhesives and fasteners
 - a. Ensure 1/8" gap around the perimeter and penetrations to allow for expansion/contraction.
 - 3. If applicable, install moldings and air vents at desired locations
 - 4. See Sustainable Flooring's complete Installation Instructions – Textura Dimensions Installation Instructions at: www.sustainableflooring.com

3.04 CLEANING and MAINTENANCE

- A. Clean and maintain in accordance with "finish" Manufacturer's recommendations (recoat as often as needed)

With any questions, or for this in a digital format, contact:

Sustainable Flooring, Inc.
5403 Western Ave #C
Boulder, CO 80301
Ph: (303) 544-6076
Email: info@sustainableflooring.com
Web: www.sustainableflooring.com