

CSI Spec. for Textura Recycled Wood Wall Panels (06 4200)

Textura Recycled Wood Panels

Part 1 – General

1.03 QUALITY ASSURANCE

A. Qualifications:

1. Installer Qualifications:
 - a. Minimum 2 years of work with the installation of products in this section.

1.04 DELIVERY, STORAGE, AND HANDLING

A. Deliver wall paneling to project site, or fabrication site, not less than 2 days prior to start of installation (to allow for suitable acclimation).

B. Environmental Requirements: Maintain and following conditions in building for minimum 7 days prior to, during and after installation of panels.

1. Temperature: 60 to 72 degrees F (16 to 22 degrees C)
2. Humidity: 25 to 55 percent

1.06 WARRANTY

A. Special Warranty:

1. Sustainable Flooring's Structural Warranty: 5 years against delamination or separation as a result of a manufacturing defect when finished and maintained in accordance with manufacturer's installation instructions.

PART 2 – PRODUCTS

2.01 MANUFACTURER

- A. Sustainable Flooring
4390 Pali Way
Boulder, CO 80301
- Tel: (303) 544-6076
Fax: (303) 447-0491
e-mail: info@sustainableflooring.com
Website: <http://www.sustainableflooring.com>

B. Substitutions: None Permitted

2.02 MATERIALS

- A. Textura Recycled
1. Available Colors
 - a. Textura Recycled **Mossy Maple**
 - b. Textura Recycled **Rustic Maple**
 - c. Textura Recycled **Midnight Maple**
 - d. Textura Recycled **Walnut**
 - e. Textura Recycled **Jungle Light**
 - f. Textura Recycled **Jungle Medium**

- g. Textura Recycled **Jungle Dark**
 - h. Textura Recycled **Cuban Oak**
2. Size: All but Jungle Mix Series are Approx. 3/8" thick x 53.5" wide x 13.5" high (thickness varies throughout pattern)
Jungle Mix (Light, Medium and Dark) are approx.. 3/8" x 12" x 60" Finish is a Natural Oil.
 3. Construction: Textura Recycled is made of decorative placed wood strips laminated onto a 3-ply birch plywood substrate
 4. Moisture content: Approx. 6 percent at maximum.
 5. Finish: Water-Based polyurethane
 6. Certifications: FSC STD-04-004
 7. Flammability: per ASTM E8
 - a. Flame Spread = 76 to 200
 - b. Smoke Developed = 0 to 450

B. Accessories

1. Contour Molding:
 - a. Size: approx. .55" x 1-1/4" x 90"
2. Baseboard:
 - a. Size: approx. .75" x 4" x 90"
3. Door and Window Molding
 - a. Size: approx. .75" 2.25" x 90"
4. Air Vents:
 - a. Size: width at 6" or 8" / Length at 12" , 14" x 24" or 30"
5. Electric Outlet Frames:
 - a. Single size: approx. 2.75" x 4.5"
 - b. Double size: approx. 4.5" x 4.5"
 - c. Triple size: approx. 6.38" x 4.5"
 - d. Quadruple size: approx. 8.13" x 4.5"

PART 3 - EXECUTION

3.01 EXAMINATION

A. Examine components and/or surface to which Textura Recycled will be mounted on, or fabricated with, ensuring components are clean, dry, flat, and free of contaminants that could potentially interfere with adhesive bond.

B. Verify that HVAC system is operating and maintaining occupancy level temperature and humidity conditions.

C. If either of the above needs attendance, coordinate with responsible entity to correct unsatisfactory conditions prior to the beginning of the installation.

3.02 PREPARATION

A. Acclimatization: Ensure that all Textura products are acclimated for a minimum of 2 days (unboxed and within the space to which the material will be installed).

3.03 INSTALLATION

A. Install in accordance with manufacturer's installation instructions.

1. Set paneling plumb, rigid and level
 - a. Ensure all penetrations and obstructions are accounted for in the layout

2. Install panels using adhesives and fasteners
 - a. Ensure 1/8" gap around the perimeter and penetrations to allow for expansion/contraction.
3. If applicable, install moldings and air vents at desired locations
4. See Sustainable Flooring's complete Installation Instructions – Textura Recycled Installation Instructions at www.sustainableflooring.com

3.04 CLEANING and MAINTENANCE

A. Clean and maintain in accordance with "finish" Manufacturer's recommendations (recoat as often as needed)

With any questions, or for this in a digital format, contact:

Sustainable Flooring, Inc.
4390 Pali Way
Boulder, CO 80301
Ph: (303) 544-6076
Fax: (303) 447-0491
Email: info@sustainableflooring.com
Web: www.sustainableflooring.com