



SUSTAINABLE
F L O O R I N G

ReCover™ Organic flooring - General Cleaning and Maintenance

Vorwerk ReCover is fitted with a very durable wear & tear layer at the factory.

This wear & tear layer requires merely a low level of care and reduces maintenance costs sustainably. Neither an introductory care phase, coating the surface with polymer dispersions or the use of care & maintenance products is necessary!

Preventive measures:

Sufficiently sized textile 'dirt walk-off zones' measuring at least 4 to 6 running meters can reduce the amount of soiling carried into the contract site by up to 80 %, and thus have a considerable influence on the utility value of the flooring and on cleaning costs.

Cleaning upon completion of construction work: Once the loose soiling (dust & debris) lying on the flooring has been removed, clinging dirt is removed manually or by machine. Red pads (3M pad) or brushes can be used for the purpose of mechanical dirt removal. Water with the addition of a suitable PU cleaner is used as a mopping solution. An introductory care phase or coating following installation of the flooring is not necessary.

Maintenance cleaning:

Vorwerk ReCover is cleaned daily or at longer intervals on a need-oriented basis. Loose dirt lying on it can be removed by sweeping, vacuum cleaning or damp mopping. Appropriate mop systems or impregnated non-woven cloths are suitable for damp mopping. In the event of heavy soiling with clinging dirt, a PU cleaner is added to the mopping water. The flooring is freed from soiling and dirt via a two-step mopping process. A suitable automatic scrubber-dryer with a red cleaning pad or a medium-bristle scrubbing brush can alternately be used.

Basic thorough cleaning: Is dispensed with!

Stain removal:

All substances that form stains or are aggressive must be removed from Vorwerk RE/COVER immediately. When treating stains with cleaning agents or stain removers, a material compatibility test must be conducted first. Attention is to be paid to the instructions and stipulations issued by the manufacturer of the cleaning agent.

General instructions:

After laying the flooring, suitable protective coverings must shield the flooring against damage in all areas where a great deal of traffic occurs during the construction phase. Any build-up of moisture underneath furnishings and fittings is to be avoided. Chair, table and furniture legs are to be safeguarded using appropriate furniture glides, pads or mats.

Whenever possible, light-colored, non-migrating furniture glides ought to be used. Use only appropriate chair and furniture castors in accordance with the DIN EN 12529 (Type "W" = soft) standard. Chair castors and glides for chairs and other furniture are to receive regular maintenance. The surfaces on which chair and furniture glides rest ought to be level and rounded at the edges. In the case of elastic floorings, heavy localized loads on a small contact area can



lead to irreversible impressions or damage. As necessary, use suitable matting or material underneath to spread the load.

The slip resistance and traction of floorings is decisively influenced by the amount of dirt carried in, the frequency of cleaning, and the cleaning or care products used. Please use only cleaning and care products from one manufacturer that have been coordinated for use with each other. Scouring powders, sanitary-ware cleansers, acids or strong solvents can lead to a damaging of the flooring surface. Colored antiseptics and skin disinfectants can cause irreversible discoloration or staining.

These instructions make no claim as to the completeness thereof. You can obtain product recommendations from the manufacturers of cleaning agents upon request.

For any additional information on the Installation and/or Maintenance, please contact:

Sustainable Flooring, Inc.
5403 Western Ave #C
Boulder, CO 80301
Ph: (303) 544-6076
www.sustainableflooring.com